

# Features



**Titanium Coils Exchanger**  
Titanium Heat exchanger effectively prevent corrosion.



**Pressure Protection**  
With high / low pressure protection, heat pump are protected at bad working condition.



**COMPRESSOR & SPAREPARTS WARRANTY**  
Guarantee for compressor and spareparts.



**ABS Casing Material**  
ELTERRA SPP Series come with ABS plastic casing material for added durability, corrosion resistance and long lasting.



**R32 Green Refrigerant**  
Less CO<sub>2</sub> emission, R32 is more environmentally friendly and has a lower GWP index than other refrigerant.



**Heating & Cooling**  
Elterra SPP Series not only heat your pool or spa but can cool it too.



**LCD Display**  
Equipped with LCD Display, this series of pool heat pumps provides users easy control experience and provides the unit fine decorations.



**Smart Control via Wifi**  
Easy control to adjust the temperature via wifi connection and iPhone.



**Cost Effective**  
The COP of this series is as high as 6.9, which saves you at least 85% energy compared with traditional electric swimming pool heating.



CONSTANTLY STABLE  
& RENEWABLE  
**HOT WATER**  
SWIMMING POOL PORTABLE  
SMART SERIES



009/RTLJUN/2026



HEAT PUMP WATER HEATER



CONSTANTLY STABLE  
& RENEWABLE

**HOT WATER**  
SWIMMING POOL PORTABLE  
SMART SERIES





HEAT PUMP WATER HEATER

## CONSTANTLY STABLE & RENEWABLE HOT WATER

Memberikan jaminan kenyamanan dalam kehidupan sehari-hari, dengan memastikan pasokan air hangat yang konsisten. Sifatnya yang dapat diperbaharui menunjukkan komitmen terhadap keberlanjutan lingkungan, guna mempromosikan kesadaran akan konsumsi energi yang berkelanjutan.

Elterra Heat Pump bukan hanya sekadar perangkat, tetapi juga merupakan mitra setia yang mengintegrasikan kesejahteraan, kehandalan, dan keberlanjutan dalam pengalaman penggunaannya sehari-hari.

### ELTERRA-HSPP Series

| Model:                                                                                                 |                       | HSPP-7                             | HSPP-9     | HSPP-11    | HSPP-15      | HSPP-25 (1PH) | HSPP-25 (3PH)     |
|--------------------------------------------------------------------------------------------------------|-----------------------|------------------------------------|------------|------------|--------------|---------------|-------------------|
| Ambient Temperature: (DB/WB) 27°C/24.3°C; Water Inlet/Outlet Temperature: 26°C/28°C.                   |                       |                                    |            |            |              |               |                   |
| Heating Capacity (kW)                                                                                  |                       | 2.17~7.48                          | 2.35~9.3   | 2.56~11.06 | 3.09~15.26   | 5.10~24.68    |                   |
| Consumed Power (kW)                                                                                    |                       | 0.12~1.15                          | 0.13~1.35  | 0.14~1.62  | 0.17~2.35    | 0.27~3.87     |                   |
| COP                                                                                                    |                       | 18.08~6.50                         | 18.08~6.89 | 18.29~6.83 | 18.18~6.49   | 18.89~6.38    |                   |
| Boost Mode                                                                                             | Heating Capacity (kW) | 7.48                               | 9.3        | 11.06      | 15.26        | 24.68         |                   |
|                                                                                                        | COP                   | 6.5                                | 6.89       | 6.83       | 6.49         | 6.38          |                   |
| Smart Mode                                                                                             | Heating Capacity (kW) | 4.87~7.48                          | 6.00~9.3   | 7.15~11.06 | 9.92~15.26   | 15.73~24.68   |                   |
|                                                                                                        | COP                   | 6.50~7.5                           | 6.89~7.91  | 6.83~7.6   | 6.49~7.5     | 6.38~7.30     |                   |
| Silent Mode                                                                                            | Heating Capacity (kW) | 4.87                               | 6          | 7.15       | 9.92         | 15.73         |                   |
|                                                                                                        | COP                   | 7.5                                | 7.91       | 7.6        | 7.5          | 7.3           |                   |
| Ambient Temperature: (DB/WB) 15°C/12°C; Water Inlet Temperature: 26°C.                                 |                       |                                    |            |            |              |               |                   |
| Heating Capacity (kW)                                                                                  |                       | 1.86~5.58                          | 1.43~6.60  | 1.76~8.05  | 2.05~10.54   | 3.47~18.4     |                   |
| Consumed Power (kW)                                                                                    |                       | 0.24~1.17                          | 0.17~1.43  | 0.21~1.63  | 0.28~2.18    | 0.41~3.85     |                   |
| COP                                                                                                    |                       | 7.75~4.77                          | 8.41~4.62  | 8.38~4.94  | 7.32~4.83    | 8.46~4.78     |                   |
| Boost Mode                                                                                             | Heating Capacity (kW) | 5.58                               | 6.6        | 8.05       | 10.54        | 18.4          |                   |
|                                                                                                        | COP                   | 4.77                               | 4.62       | 4.94       | 4.83         | 4.78          |                   |
| Smart Mode                                                                                             | Heating Capacity (kW) | 3.62~5.58                          | 4.29~6.6   | 5.23~8.05  | 6.85~10.54   | 11.96~18.4    |                   |
|                                                                                                        | COP                   | 4.77~5.3                           | 4.62~5.2   | 4.94~5.5   | 4.83~5.4     | 4.78~5.3      |                   |
| Silent Mode                                                                                            | Heating Capacity (kW) | 3.62                               | 4.29       | 5.23       | 6.85         | 11.96         |                   |
|                                                                                                        | COP                   | 5.3                                | 5.2        | 5.5        | 5.4          | 5.3           |                   |
| Power Supply                                                                                           |                       | 220-240V~/50Hz                     |            |            |              |               | 380-415V/3N~/50Hz |
| Performance Condition: Ambient Temperature: (DB/WB) 35°C/-; Water Inlet/Outlet Temperature: 30°C/28°C. |                       |                                    |            |            |              |               |                   |
| Cooling Capacity (kW)                                                                                  |                       | 1.78~3.72                          | 1.92~5.12  | 2.48~5.94  | 1.88~5.01    | 4.74~12.66    | 4.74~12.66        |
| EER                                                                                                    |                       | 8.09~4.43                          | 8.00~4.20  | 8.00~3.86  | 8.17~2.77    | 7.90~3.05     | 7.90~3.05         |
| Boost Mode                                                                                             | Cooling Capacity (kW) | 3.72                               | 5.12       | 5.94       | 5.01         | 12.66         | 12.66             |
|                                                                                                        | EER                   | 4.43                               | 4.20       | 3.86       | 2.77         | 3.05          | 3.05              |
| Smart Mode                                                                                             | Cooling Capacity (kW) | 2.42~3.72                          | 3.32~5.12  | 3.86~5.94  | 3.25~5.01    | 8.23~12.66    | 8.23~12.66        |
|                                                                                                        | EER                   | 4.43~4.60                          | 4.20~4.50  | 3.86~4.00  | 2.77~3.00    | 3.05~3.35     | 3.05~3.35         |
| Silent Mode                                                                                            | Cooling Capacity (kW) | 2.42                               | 3.32       | 3.86       | 3.25         | 8.23          | 8.23              |
|                                                                                                        | EER                   | 4.60                               | 4.50       | 4.00       | 3.00         | 3.35          | 3.35              |
| Max Power Input (kW)                                                                                   |                       | 1.2                                | 1.6        | 1.9        | 3.1          | 4.9           |                   |
| Max Current(A)                                                                                         |                       | 6.82                               | 9.1        | 10.8       | 14.1         | 22.3          | 12.9              |
| Heating Temperature Range(°C)                                                                          |                       | 15~40                              |            |            |              |               |                   |
| Max Water Temperature (°C)                                                                             |                       | 40                                 |            |            |              |               |                   |
| Cooling Temperature Range(°C)                                                                          |                       | 8~28                               |            |            |              |               |                   |
| Running Temperature Range(°C)                                                                          |                       | -15~43                             |            |            |              |               |                   |
| Advised Swimming Pool Size(m³)                                                                         |                       | 15~30                              | 20~40      | 25~50      | 30~60        | 55~90         |                   |
| Refrigerant                                                                                            |                       | R32                                |            |            |              |               |                   |
| Compressor Qty.                                                                                        |                       | 1                                  |            |            |              |               |                   |
| Compressor Brand                                                                                       |                       | MITSUBISHI ELECTRIC ( DC Inverter) |            |            |              |               |                   |
| Air Side Heat Exchanger                                                                                |                       | Hydrophilic Fin Exchanger          |            |            |              |               |                   |
| Water Side Heat Exchanger                                                                              |                       | Titanium Tube Heat Exchanger       |            |            |              |               |                   |
| Expansion Valve                                                                                        |                       | Electronic Expansion Valve         |            |            |              |               |                   |
| Water Flow(m³/h)                                                                                       |                       | 3.1                                | 4          | 4.73       | 6.6          | 10.8          |                   |
| Water Pressure Drop (kPa)                                                                              |                       | 5                                  | 16         | 18         | 15           | 59            |                   |
| Air Flow Direction                                                                                     |                       | Horizontal                         |            |            |              |               |                   |
| Net Dimension LxWxH (mm)                                                                               |                       | 907×353×616                        |            |            | 1000×399×658 | 1115×455×765  |                   |
| Water Pipe Connection (Inlet /Outlet)(mm)                                                              |                       | 50                                 |            |            |              |               |                   |
| Net Weight (kg)                                                                                        |                       | 44                                 | 46         | 48         | 53           | 80            | 82                |
| Noise dB(A)                                                                                            |                       | 31~44                              | 32~46      |            | 33~47        | 34~51         |                   |
| Electric Shock Proof                                                                                   |                       | I                                  |            |            |              |               |                   |
| Water Proof Level                                                                                      |                       | IPX4                               |            |            |              |               |                   |